

www.epoxyinternational.com

Epoxy International

Email: <u>info@epoxyinternational.com</u> 200 Allens Ave, Providence, RI 02903

Phone: (888) 522-6742 - Fax: (877) 522-6742

Disclaimer: The information in this SDS relates to the product named and is based upon information Epoxy International considers to be accurate. No warranty expressed or implied is intended. This information is offered exclusively for your consideration and interpretation. The Corporate Safety and Environmental Affairs Department is responsible for the preparation of this Safety Data Sheet.

Safety Data Sheet

Epoxy International THERMAL-GREASE 4 SDS Number: 04
SDS Date: 09/27/2015

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product name: THERMAL-GREASE 4

SDS number: 04
Product type: Grease

Chemical family: Silicone Grease
Company Address: Epoxy International
200 Allens Ave,

Providence, RI 02903

Email: info@epoxyinternational.com

 Emergency Contact Number :
 (888) 522-6742

 Fax:
 (877) 522-6742

 Chemtrec (Domestic):
 (800) 424-9300

 Chemtrec (International):
 (703) 527-3887

SECTION 2: HAZARDS IDENTIFICATION

Form: Viscous Liquid

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard Communications

Standard (29 CFR 1910.1200)

Emergency overview: WARNING!

CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY

CAUSE RESPIRATORY TRACT IRRITATION. HEAD MATERIAL CAN CAUSE

THERMAL BURNS.

Potential acute health effects:

Inhalation: Slightly irritating to the respiratory system.

Ingestion: Not expected to be harmful under normal conditions of use.

Skin: Irritating to skin. May cause sensitization by skin contact material. Can cause

thermal burns.

Eyes: Irritating to eyes. Heated material can cause thermal burns.

Potential chronic health effects:

Chronic effects:

No known significant effects or critical hazards.

Carcinogenicity:

No known significant effects or critical hazards.

Mutagencity:

No known significant effects or critical hazards.

Teratogenicity:

No known significant effects or critical hazards.

Developmental effects:

No known significant effects or critical hazards.

Fertility effects:

No known significant effects or critical hazards.

Epoxy International

Target organs: Review section 2 and 11 for any additional assessments.

Over-exposure signs/symptoms

Inhalation: Adverse symptoms may include the following respiratory tract irritation

coughing.

Skin: Adverse symptoms may include the following: irritation and or redness

Eyes: Adverse symptoms may include the following: pain and or irritation, watering

and redness.

SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS

| Ingredient's name | CAS NUMBER | % BY WEIGHT |
|-----------------------|---------------------|-------------|
| Zinc Oxide | 215-222-5 | >70 |
| Siloxanes & Silicones | Y Polymer Exemption | <30 |

^{**}Any applicable Canadian trade secret numbers will be listed in section 15.

SECTION 4: FIRST AID MEASURES

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and

lower eyelids. Check for and remove any contact lenses. Get medical attention.

Skin contact: Flush contaminated skin with a plenty of water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wears gloves, continue to rinse for at least 10 minutes. In the event of any complains or symptoms, avoid further exposure. Wash clothing before reuse. For contact with hot product flush contaminated skin with large amounts of cold water to dissipate heat. Gear with clean cotton sheeting or gauze. Get medical attention

immediately.

Inhalation: Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Ingestion: Wash out mouth with water. Remove dentures if any. Move person to fresh air. Keep person warm

and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting is dangerous. Do not induce vomiting unless directed to do so medical personnel If vomiting occurs, the head should be kept low that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

Protection of First Aid

personnel:

In the event of body contact. Treat symptomatically. Contact poison treatment specialist immediately

if large quantities have been ingested or inhaled.

Notes to physician: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

SECTION 5: FIRE FIGHTING MEASURES

FLAMMABILITY OF THE

In a fire or if heated, a pressure increase will occur and the container may burst.

PRODUCT:

EXTINGUISHING MEDIA

Suitable: Use an extinguishing agent suitable for the surrounding fire.

Not suitable: N/A

Special exposure hazards: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Hazardous Combustion

Decomposition products may include the following materials: carbon oxides.

Products:

Special protective equipment: Fire-fighters should wear appropriate protective equip self-contained breathing apparatus (SCBA)

with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate

surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective

equipment (see section 8).

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, drains and sewers. Inform the

relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or

air).

Large spill: Stop leak if without risk. Move containers from spill area. For molten material, allow the product to

cool and solidify. Vacuum or sweep up material and place in a designated, labeled waste container.

Dispose of via a licensed waste disposal contractor.

Small spill Use an extinguishing agent suitable for the surrounding fire.

SECTION 7: HANDLING AND STORAGE

Handling:

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processes. Workers should wash hands and face before eating, drinking or smoking. Persons with history of skin sensitization problems should not be employed in any process in which this product is used. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material,

Epoxy International

^{*}For safety and environmental precautions, please review entire SDS for necessary information.

| | kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|----------|--|
| Storage: | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Note: This resin may be handled, shipped and stored at elevated temperature in bulk. |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| CONSULT LOCAL AUTHORITI | ES FOR ACCEPTABLE EXPOSURES LIMITS |
|------------------------------------|---|
| Ventilation: | Use only with adequate ventilation. If user operations generate dust, fumes gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
| Eyes: | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. |
| Skin: | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Clothing measures: | Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance. Uniforms, coveralls, or a lab coat should be worn. |
| HYGIENE MEASURES: | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to workstation location. |
| Respiratory measures: | Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels. the hazards of the products of the safe working limits of the selected respirator. |
| Recommended monitoring procedures: | If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. |
| Environmental exposure controls: | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

GENERAL INFORMATION:

| PHYSICAL FORM | Liquid |
|----------------------------|----------------|
| COLOR | White |
| ODOR | Slight Odor |
| BOILING POINT | NA |
| FLASH POINT: | >93°C, >200 °F |
| SOLUBILITY IN WATER | Not Soluble |
| SPECIFIC GRAVITY (WATER=1) | 2.39 |

 $\textbf{Email:} \ \underline{info@epoxyinternational.com}$

| VAPOR PRESSURE | Negligible |
|-------------------------|------------|
| VAPOR DENSITY (AIR = 1) | >Air |
| VOLATILES VOLUME | 0 |
| SHELF LIFE: | 6 MONTHS |

SECTION 10: STABILITY AND REACTIVITY

| Stability: | The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur. |
|--------------------------|---|
| Materials to avoid: | Reactive or incompatible with the following materials: Oxidizers, Acids, Amines |
| Conditions to avoid: | Strong oxidizer. |
| Hazardous decompositions | Decomposition products may include the following materials: Carbon Oxides. |
| products: | |
| Hazardous polymerization | CONDITIONS Heat may cause hazardous polymerization. |
| conditions: | |
| Reactivity: | Stable under normal conditions |
| Other hazards: | Reacts with considerable heat release with some curing agents. |

SECTION 11: TOXICOLOGICAL INFORMATION

| Primary Entry Route(s): | | Skin, eyes, inhalation. | |
|-------------------------|-----------------|-------------------------|--|
| Skin irritation: | | | |
| | SKIN RABBIT: | 500g/kg | |
| Eye irritation: | | | |
| | EYE RABBIT: | 500 MG | |
| Acute toxicity: | | | |
| | LD50 (Oral Rat) | >8437 mg/kg | |
| TCLo (Human Inhalation |) | 600 mg/kg | |
| TDLo (Human Oral) TDLo |) | 500 mg/kg | |
| (Intratracheal/rat) | | 250 mg/kg | |
| Other information: | | | |

OEL-RUSSICA: TWA 6 mg/m3, JUNE 2003 AIN

Only selected Registry of Toxic Effects if Chemical substances (RTECS) data is presented here. See actual entry in RTECS for complete information.

SECTION 12: ECOLOGICAL INFORMATION

| Environme | ental effects |
|-----------|---|
| No knov | wn significant effects or critical hazards. |
| Other ac | lverse effects |
| No know | vn significant effects or critical hazards. |

SECTION 13: DISPOSAL INFORMATION

Waste The generations of waste should be avoided or minimize wherever possible. Dispose of surplus and non-recyclable disposal: products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local

authority requirements. Avoid dispersal of spilled and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORTATION INFORMATION

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

| Regulatory Information | UN/NA Number | Proper shipping name | Classes/Packaging Group | Reportable Quantity (RQ) |
|---------------------------|-----------------|----------------------|-------------------------|--------------------------|
| CFR | non-regulated | non-regulated | non-regulated | non-regulated |
| IATA (Cargo) | non-regulated | non-regulated | non-regulated | non-regulated |
| TDG | non-regulated | non-regulated | non-regulated | non-regulated |
| IMO/IMDG | non-regulated | non-regulated | non-regulated | non-regulated |

SECTION 15: REGULATORY INFORMATION

| | | |
|-----------------------|------|--|
| US Regulations | | |

HCS Irritating materials, sensitizing material

Classification:

Canada Class D-2B: Material causing other toxic effects (Toxic).

(WHMIS): Canada lists: Canadian NPRI: None Required

China (IECSC) On the IECSC inventory

US Federal SARA 311/312 classification immediate (acute) health hazard.

Regulations

SARA 313 – Supplier Notification

This product contains the following toxic chemical(s) subject

to the reporting requirements of section 313 of Title 3 of the Superfund Amendments and Reauthorization Act of

1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.

None required.

SARA 302 Extremely Hazardous Substances None Required

State Regulatic Massachusetts RTK Substances None Required

New Jersey RTK SubstancesNone RequiredPennsylvania RTK Hazardous SubstancesNone Required

California Prop. 65 WARNING: This Product contains a chemical

know to the state of California to cause cancer. Oxirane. (Phenoxymethyl) –122-60-1

InternationalEurope inventoryall components are listed or exempted.RegulationsAustralia inventory (AICS)all components are listed or exempted.

Australia inventory (AICS) all components are listed or exempted.

China inventory (IECSC) all components are listed or exempted.

Korea inventory (KECI) all components are listed or exempted.

Philippines inventory (PICCS)

Japan inventory (ENCS)

Canada inventory

United States inventory (TSCA 8b)

New Zealand inventory (NZIoC)

all components are listed or exempted.

all components are listed or exempted.

Not determined.

WARNING: This product contains the following chemicals that are known to the State of California to cause cancer, birth defects or other reproductive harm. Unless a concentration is specified in Section 2 of the SDS, the below chemical/s are present in trace amounts.

ComponentCAS NumberNone reportableN/A

SECTION 16: REGULATORY INFORMATION

HMIS® Hazard Ratings

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs by OSHA's 29 CFR 1910.1200, we choose to provide them as a service to our customers using HMIS®. These ratings are to be used only with a fully implemented HMIS® program. To deal adequately with the safe handling of this material, all the information contained in this SDS must be considered.

NPCA recommends that employers must determine appropriate PPE for the actual conditions under which this product is used in their workplace. For information on PPE codes, consult the HMIS® Implementation Manual.

When two ratings are provided for Health, the first represents the material 'as supplied', and the second represents the material 'in use'.

* = chronic health hazard

HMIS® is a registered trademark of the National Paint and Coatings Association (NPCA).

| Health | Flammability | Physical Hazard |
|--------|--------------|-----------------|
| 2 | 1 | 0 |

Notice to reader:

The information provided herein was believed by Epoxy International to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply suitability of the product for its intended use. All products supplied by Epoxy International are subject to Epoxy International' terms and conditions of sale. EPOXY INTERNATIONAL MAKES NO WARRANTY, EXPRESSED OR FOR ANY PURPOSE OF CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY EPOXY INTERNATIONAL, except that the product shall conform to Epoxy International specifications. Nothing contained herein constitutes an offer for the sale of any product.